

full line

PH ELECTRODE

Model : PE-03, PE-11, PE-01

ISO-9001, CE, IEC1010

PE-06HD, PE-04HD, PE-03K7, PE-05T



PE-11

PE-03

PE-01

PE-06HD

PE-05T

PE-03K7



PE-6HD



LUTRON ELECTRONIC

The Art of Measurement

full line

pH ELECTRODE

PH ELECTRODE Model : PE-03	<ul style="list-style-type: none">* General purpose, laboratory and field usage.* 12.3 mm dia. x 160 mm.* Epoxy body, 1 - 13 pH.
PH ELECTRODE Model : PE-11	<ul style="list-style-type: none">* General purpose, laboratory and field usage.* 10 mm dia. x 130 mm.* Epoxy body.* 1 - 13 pH. (0 - 14 pH typical)
PH ELECTRODE	<ul style="list-style-type: none">* Professional, laboratory and field usage.* 9.5 mm dia. x 130 mm.* Epoxy body.* 0 - 14 pH.
SPEAR TIP PH ELECTRODE Model : PE-06HD PE-04HD	<ul style="list-style-type: none">* The "Spear Tip pH electrode" is perfect for those pH measurements in applications where sample piercing is required. Meat, sausage and cheese are ideal applications. The electrode features a very durable glass measuring spear packaged in a rugged virtually unbreakable epoxy body.* Range : 0 to 14 pH (PE-04HD)* Range : 1 to 13 pH (PE-06HD)
pH ELECTRODE + Temp. PROBE (combination kit of pH electrode) Model : PE-03K7	<ul style="list-style-type: none">* One kit combine of PH electrode PE-03 and Temp. probe TP-07 as a whole unit.* Easy operation for the pH measurement under the ATC (Automatic Temp. Compensation).* Available for PH-208, PH-207, PH-207HA, PH-221 YK-2005WA.
pH electrode build in Temp. thermister inside. Model : PE-05T	<ul style="list-style-type: none">pH electrode build in Temp. thermister inside.* pH meter when make the temperature compensation,* the extra optional Temp. probe is not necessary.Available for PH-207, PH-208, PH-207HA, PH-221, YK-2005WA,General purpose, laboratory & field usage. 1 to 13 pH (typical 0 to 14 pH).pH Operation Temp. : 5 to 60 °C (41 to 140 °F).* Temp. Probe Range : 0 to 60 °C (32 to 140 °F).* Epoxy Body Material.* Connector :* BNC plug for pH, ear phone plug for Temp.

* Appearance and specifications listed in this brochure are subject to change without notice. 0609-PHELECTRODE