

full line

# PH ELECTRODE

Model : PE-03, PE-11, PE-01

ISO-9001, CE, IEC1010

PE-06HD, PE-04HD, PE-03K7, PE-05T



PE-11

PE-03

PE-01

PE-06HD

PE-05T

PE-03K7



PE-6HD

**Lutron**

**LUTRON ELECTRONIC**

*The Art of Measurement*

*full line*

# pH ELECTRODE

PH ELECTRODE Model : PE-03	<ul style="list-style-type: none"><li>* General purpose, laboratory and field usage.</li><li>* 12.3 mm dia. x 160 mm.</li><li>* Epoxy body, 1 - 13 pH.</li></ul>
PH ELECTRODE Model : PE-11	<ul style="list-style-type: none"><li>* General purpose, laboratory and field usage.</li><li>* 10 mm dia. x 130 mm.</li><li>* Epoxy body.</li><li>* 1 - 13 pH. (0 - 14 pH typical)</li></ul>
PH ELECTRODE	<ul style="list-style-type: none"><li>* Professional, laboratory and field usage.</li><li>* 9.5 mm dia. x 130 mm.</li><li>* Epoxy body.</li><li>* 0 - 14 pH.</li></ul>
SPEAR TIP PH ELECTRODE  Model : PE-06HD PE-04HD	<ul style="list-style-type: none"><li>* The "Spear Tip pH electrode" is perfect for those pH measurements in applications where sample piercing is required. Meat, sausage and cheese are ideal applications. The electrode features a very durable glass measuring spear packaged in a rugged virtually unbreakable epoxy body.</li><li>* Range : 0 to 14 pH (PE-04HD)</li><li>* Range : 1 to 13 pH (PE-06HD)</li></ul>
pH ELECTRODE + Temp. PROBE ( combination kit of pH electrode )  Model : PE-03K7	<ul style="list-style-type: none"><li>* One kit combine of PH electrode PE-03 and Temp. probe TP-07 as a whole unit.</li><li>* Easy operation for the pH measurement under the ATC ( Automatic Temp. Compensation ).</li><li>* Available for PH-208, PH-207, PH-207HA, PH-221 YK-2005WA.</li></ul>
pH electrode build in Temp. thermister inside.  Model : PE-05T	<ul style="list-style-type: none"><li>pH electrode build in Temp. thermister inside.</li><li>* pH meter when make the temperature compensation,</li><li>* the extra optional Temp. probe is not necessary.</li><li>Available for PH-207, PH-208, PH-207HA, PH-221, YK-2005WA,</li><li>General purpose, laboratory &amp; field usage. 1 to 13 pH ( typical 0 to 14 pH ).</li><li>pH Operation Temp. : 5 to 60 °C ( 41 to 140 °F ).</li><li>* Temp. Probe Range : 0 to 60 °C ( 32 to 140 °F ).</li><li>* Epoxy Body Material.</li><li>* Connector :</li><li>* BNC plug for pH, ear phone plug for Temp.</li></ul>

\* Appearance and specifications listed in this brochure are subject to change without notice. 0609-PHELECTRODE