battery type: Alkaline Manganese Dioxide

battery size: A27 (27A)

chemical system: Zn / KOH-H₂O / MnO₂

Conditions

nominal voltage: 12 V

open circuit voltage: 12.3...12.9 V new battery

12.2...12.9 V after 1 year storage at 20°C

all measurements at 22 ± 2°C ambient

capacity

rated: 20 mAh discharge under 20kΩ load; 24hours/day

End Voltage (EV): 6.0V

minimum: 18 mAh discharge under 20kΩ load; 24hours/day

End Voltage (EV): 6.0V

Standard discharge time

nominal: 38 h at $20k\Omega$ load new battery

EV: 6.0V

for QC measurement (at 20kΩ load; E.V.6.0V)

minimum: 35 h tested within 30 days after delivery

32 h after 12 months storage at room temperature

Discharge currents

standard: 0.06 mA


max. recommended current


under continuous discharge: 0.5 mA

max. recommended current

under pulse discharge: 5 mA

Discharge diagrams:






shelf life: 3 years under proper storage conditions (ta: ≤ 22°C; RH: 60 ± 15%) ≤90 % of the capacity will remain after 12 months storage

operating temperature

range: - 20...60 °C

mechanical specifications:



A27 12V

A27 PA27

A27 | LR27 | MN27 | L828

blister card

dimensions: 55 x 70mm

weight:

6.2g (incl. battery)

nominal weight: 4.4 g

ANSMANN°

ANSMANN Specifications for model:	A27 Alkaline Battery blister package
data sheet no. / part no.	1516-0001
supplier no.	701381
author / date	TG / 18.06.2013