



Model: LP852040		Min. Capacity 最低容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)	570	Overcharge Detection Voltage (V) 过充保护电压 (V)	4.28±0.05
Battery pack specification (电池组规格)		Typical Capacity 典型容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)	620	Overdischarge Detection Voltage (V) 过放保护电压 (V)	3.0±0.1
		Nominal Voltage 标称电压 (V)	3.7	Limited to Max loading current 仅用于最大的负载电流 peak value (A) 峰值 0.5 (A)	constant (A) 持续 0.2 (A)
		Internal impedance 内阻 (≦) (m Ω, AC 1KHz)	200	Customer required Max loading current 客户要求最大的负载电流 peak value (A) 峰值 0.5 (A)	constant (A) 持续 0.2 (A)
Ambient Conditions (环境温度)		Charge Temp. 充电温度 (°C)	0~45	Battery protection (相关的电池保护值) If actual application loading current is bigger than EEMB suggested rate PCM design. (如果实际应用的负载电流大于EEMB提供值, 请提出来, 实际的应用请识别PCM的设计至关重要)	
		Discharge Temp. 放电温度 (°C)	-20~60°		
		Humidity (湿度)	65±20%		

Remark(备注):
 1. No scratch, discoloration, discoloration and leakage on the appearance of the cell/电池表面无划痕、变形、污点及漏液等现象。
 2. Rols compliant(严格按照ROHS要求生产)。

Title		LP852040-PCM-LD	
File NO.		A17177	
EEMB BATTERY		EEMB BATTERY	
Drawn:	YanF	Approved2:	
Group:	Group 19	Draw Date:	2019/05/24
Approved1:		Scale:	1 : 2
Projection:		Unit:	mm
Page:	1/1		
Revise No.:			
E4-2009			