



# VoltGo Elite Series Lithium Compatible Inverters

Model	Peak Power (W)	Minimum Battery Voltage (V)	Peak Current (A)	Minimum Number of 12V 100Ah (100A/each)	Minimum Number of 12V 200Ah (150A/each)	Minimum Number of 12V 400Ah (250A/each)	Minimum Number of 24V 100Ah (150A/each)	Minimum Number of 24V 200Ah (200A/each)	Minimum Number of 48V 100Ah (100A/each)
EasyPlus 12/1600/70	3000	10	300.00	3	2	2	-	-	-
MultiPlus II 12/3000/120 -32	5500	10	550.00	6	4	3	-	-	-
MultiPlus II 24/3000/70 - 32	5500	22.4	245.54	-	-	-	2	2	-
MultiPlus II 48/3000/35 - 32	5500	44.8	122.77	-	-	-	-	-	2
MultiPlus II 12/5000/220 - 50A	9000	10	900.00	9	6	4	-	-	-
MultiPlus II 24/5000/120 - 50A	9000	22.4	401.79	-	-	-	3	2	-
MultiPlus II 48/5000/70 - 50	9000	44.8	200.89	-	-	-	-	-	2
MultiPlus II 48/8000/110 -100	15000	44.8	334.82	-	-	-	-	-	4
MultiPlus II 48/10000/140 - 100	18000	44.8	401.79	-	-	-	-	-	4
MultiPlus II 48/15000/200-100	27000	44.8	602.68	-	-	-	-	-	6
MultiPlus II 24/3000/70-32	5500	22.4	245.54	-	-	-	2	2	-
MultiPlus II 48/3000/35 -32GX	5500	44.8	122.77	-	-	-	-	-	2
MultiPlus II 48/5000/70 -50GX	9000	44.8	200.89	-	-	-	-	-	2
Quattro 12/3000/120	6000	10	600.00	6	4	3	-	-	-
Quattro 24/3000/70	6000	22.4	267.86	-	-	-	2	2	-
Quattro 12/5000/220	10000	10	1000.00	10	7	4	-	-	-
Quattro 24/5000/120	10000	22.4	446.43	-	-	-	3	3	-
Quattro 48/5000/70 -50/50	10000	44.8	223.21	-	-	-	-	-	3
Quattro 24/8000/200	16000	22.4	714.29	-	-	-	5	4	-
Quattro 48/8000/110	16000	44.8	357.14	-	-	-	-	-	4
Quattro 48/10000/140	20000	44.8	446.43	-	-	-	-	-	5
Quattro 48/15000/200	25000	44.8	558.04	-	-	-	-	-	6
Quattro II 24/5000/120	9000	22.4	401.79	-	-	-	3	2	-
Quattro II 48/5000/70 -50	9000	44.8	200.89	-	-	-	-	-	2