

Application	
Ambient temperature	-25°C ~ +50°C
Relative humidity	0 ~ 90%
Altitude above sea level	≤2000m
Compliance	IEC/EN 61439-2 IP65
Electrical	
Rated op. voltage Ue	DC1500V
Rated insulation voltage Ui	DC1500V
Rated impulse withstand voltage Uimp	12KV
Earthing	Yes
No. of String (input)	Up to 10
Input Protection	Fuse on both Negative and Positive
	Fuse-links size 10*85mm
	20A, 25A, 30A
No. of Output	1
Output Protection	Switch-disconnector with terminal cover
	350A (DC-PV2 1500V)
	Internal rotary handle
Surge Protection	SPD PV Type II
Monitoring	No
Enclosure	
Material	EG Steel or Stainless Steel
Dimension (H * W * D)	850 * 500 * 300 mm
Thickness	2mm
Degree of Protection	IP65
Finishing	Epoxy powder coating with thickness 80um
Anti-corrosion ISO12944	C5
Colour	PANTONE Cool Gray 3 CP
String input	Gland or MC4 Connector
Mounting	Wall mount Lugs

String Combiner Box (1500Vdc)

10-IN 1-OUT

- Compliant to IEC/EN 61439-2 and AS/NZS 5033
- All components are rated at 1500Vdc
- Up to 10 strings input
- Single output with one DC-PV2 rated switch disconnector
- Input fuse protection (fuse included)
- Wall mounted with metal lugs
- Two options for enclosure materials (EG Steel or Stainless Steel)
- Suitable for Fronius Tauro, Goodwe ETC inverters

Main Components			
No.	Item	Model	Quantity
1	Switch Disconnector	Noark EX9IZ 630A HV 11 350A	1
2	Surge Arrestor	Noark EX9UEP 20R 3P 1500V	1
3	Fuse Holders	Noark EX9FP30H	20
4	Incoming Fuse	Noark EX9FP30 30H	20
5	Incoming Glands	M12X1.5	20
6	Outgoing Gland	M50X1.5	1
7	Earth Wire Gland	M16X1.5	1