

Lithium SuperPack NG Compatible Inverters

Model	Peak Power (W)	Minimum Battery Voltage (V)	Peak Current (A)	Minimum Number of 12V 100Ah	Minimum Number of 12V 200Ah	Minimum Number of 24V 100Ah	Minimum Number of 24V 200Ah	Minimum Number of 48V 100Ah
EasyPlus 12/1600/70	3000	11.2	267.86	2	1	-	-	-
MultiPlus II 12/3000/120-32	5500	11.2	491.07	3	2	-	-	-
Multiplus II 24/3000/70-32	5500	22.4	245.54	-	-	2	1	-
MultiPlus II 48/3000/35-32	5500	44.8	122.77	-	-	-	-	1
MultiPlus II 12/5000/220-50	9000	11.2	803.57	4	2	-	-	-
MultiPlus II 24/5000/120-50	9000	22.4	401.79	-	-	2	1	-
MultiPlus II 48/5000/70-50	9000	44.8	200.89	-	-	-	-	1
MultiPlus II 48/8000/110-100	15000	44.8	334.82	-	-	-	-	2
MultiPlus II 48/10000/140-100	18000	44.8	401.79	-	-	-	-	2
MultiPlus II 48/15000/200-100	27000	44.8	602.68	-	-	-	-	3
Multiplus II 24/3000/70-32	5500	22.4	245.54	-	-	2	1	-
MultiPlus II 48/3000/35-32GX	5500	44.8	122.77	-	-	-	-	1
MultiPlus II 48/5000/70-50GX	9000	44.8	200.89	-	-	-	-	1
Quattro 12/3000/120	6000	11.2	535.71	3	2	-	-	-
Quattro 24/3000/70	6000	22.4	267.86	-	-	2	1	-
Quattro 12/5000/220	10000	11.2	892.86	4	2	-	-	-
Quattro 24/5000/120	10000	22.4	446.43	-	-	3	2	-
Quattro 48/5000/70	10000	44.8	223.21	-	-	-	-	2
Quattro 24/8000/200	16000	22.4	714.29	-	-	4	2	-
Quattro 48/8000/110	16000	44.8	357.14	-	-	-	-	2
Quattro 48/10000/140	20000	44.8	446.43	-	-	-	-	3
Quattro 48/15000/200	25000	44.8	558.04	-	-	-	-	3
Quattro II 24/5000/120	9000	22.4	401.79	-	-	2	1	-
Quattro II 48/5000/70	9000	44.8	200.89	-	-	-	-	1