RRC-SMB-UBC

Standard battery charger
for smart batteries

P/N: 100485



Features:

- 60W Single bay fast charger
- For the standard battery form factors RRC20xx or smart batteries with a similar footprint
- Optimized charging process for RRC batteries
  - Longer cycle life
  - Faster charging
- Simple operation – Plug and Play
- Automatic recognition and calibration of smart battery learned capacity
- External power supply for worldwide use
- Country specific AC input cables available

Applications:

Standard charging station for mobile devices used in medical, industrial and consumer markets

Talk to our engineers +61 2 9519 1200 · info@mibattery.com.au · mibattery.com.au

Specification

Input	
Voltage range	19.00 – 26.00VDC
Current	3.40A max.
Power	65.00W
Protection	Over current (fuse protected), under voltage

Output	
Voltage range	0 - 17.40VDC
Current range	0 - 4.80A
Voltage tolerance	±1% max.
Current tolerance	±10% max. @1.00A, ±3% max. @4.00A
Charge power	60.00W max.
Protection	Short circuit, over temperature shutdown, input-/output over current

Environmental	Operation:	Storage:
Ambient Temperature	0°C to 40°C	-30°C to 80°C
Pressure and Altitude	1060hPa to 795hPa -382m to 2000m	1060hPa to 533hPa -382m to 5000m
Humidity (non-condensing)	8% to 90% r.H.	5% to 95% r.H.

General	
Efficiency	~95% at 100% load
Indicator	Multi-color LED (green, red, orange)
Battery types	Standard battery form factors RRC20x or smart batteries with a similar footprint
Green procurement	RoHS 2011/65/EU + 2015/863/EU REACH 1907/2006 WEEE 2012/19/EU Chinese RoHS
Cooling	convection cooled

LED Indications	
One time Red/Orange/Green	Self-test: Charger is ready for use.
Red/Green blinking	Battery recognition and initialization.
Orange blinking	The battery is currently being calibrated.
Orange light	The inserted battery is of the correct type and is currently being charged.
Green light	The battery is charged and can be removed for use.
Red blinking	The battery is too hot or too cold to be charged without damage. If the battery is too cold it will be charged as soon as it has warmed up sufficiently. If the battery is too hot it should be removed to cool down.
Red light	The battery is damaged or it is a conventional battery which cannot be recharged.

Charger Mechanical Details	
Housing dimensions (LxWxH)	151 x 90 x 43mm
Weight	198g (excluding power supply)

Safety & EMC	In combination with included external AC/DC power supply	
Regulatory approvals	Europe International	EN62368-1 (CE) IEC62368-1 (CB)
Electromagnetic Emissions	Europe USA	EN55011, EN55032, level B FCC15 class B
Electromagnetic Immunity	ESD immunity Electromagnetic field immunity EFT / Burst Surge Conducted Immunity Magnetic Fields Voltage dips, short instrumentations & voltage variations Immunity characteristics	EN/IEC61000-4-2 EN/IEC61000-4-3 EN/IEC61000-4-4 EN/IEC61000-4-5 EN/IEC61000-4-6 EN/IEC61000-4-8 EN/IEC61000-4-11 EN55024

Talk to our engineers +61 2 9519 1200 · info@mibattery.com.au · mibattery.com.au

Specification external AC/DC power supply

Input	
Voltage range	100.00 – 240.00VAC ±10%, 50-60Hz
Current	1.70A max.
Stand by power	< 0.21W @ no load

Output	
Voltage range	19.00VDC ± 5%; Ripple < 300mV$_{pk-pk}$
Power	65.00W max.
Current range	3.42A max.
Protection	Short circuit, over voltage, over current, over temperature

General	
Efficiency	California's Energy Efficiency Level VI
Ripple & Noise	300mV (p-p)

Power Supply Mechanical Details	
Standard output connector	DC barrel jack, 5.5 x 2.5 x 11mm
Housing dimensions (LxWxH)	95 x 50 x 25.4mm
Weight	270g
Cable length	1600mm ±50mm

Regulatory Approvals		
Approvals	Europe	CE
	International	CB
	USA & Canada	cULus
	Australia & New Zealand	RCM
	Russia (Customs Union)	EAC
	Korea	KC
	China	CCC
	Japan	PSE
	India	BIS
	Taiwan	BSMI
	Mexico	NOM
	Argentina	IRAM
	South Africa	SABS
	Singapore	Safety Mark
	United Kingdom	UKCA
	Morocco	CMIM

Talk to our engineers +61 2 9519 1200 · info@mibattery.com.au · mibattery.com.au

Recommended Accessories

Type	Product	P/N	Application
3-pol AC-Cable 	US-Version EU-Version UK-Version AU-Version CN-Version	210950 210951 211133 211134 211959	Country specific power cable for standard battery chargers from RRC and PS65.
Car Adapter DC/DC 	RRC-SMB-CAR	110041	90W car adapter with USB charging port. Power suppling in cars and trucks for standard battery chargers and power management modules from RRC or mobile devices.

Germany/HQ
RRC power solutions GmbH

Technologiepark 1
66424 Homburg / Saar

+49 6841 98090
sales@rrc-ps.com

USA
RRC power solutions Inc.

18340 Yorba Linda Blvd.,
107-437
Yorba Linda, CA 92886

+1 714 777 3604
usa@rrc-ps.com

Hong Kong
RRC power solutions Ltd.

S-V,6/F, Valiant Industrial Centre 2-12
Au Pui Wan Street
Fo Tan, N.T., Hong Kong

+852 2376 0106
hkrrc@rrc-ps.cn

China
RRC power solutions Ltd.

Room 1306, C Building, Tianan International Building, Renmin South Road, Luohu District, Shenzhen 518021

+86 755 8374 1908
hkrrc@rrc-ps.cn

Vietnam
RRC Power Solutions Company Ltd.

Block C, Lot CN4
Dinh Vu – Cat Hai Economic Zone,
Dong Hai 2 Ward
Hai An District 180000
Hai Phong City

vietnam@rrc-ps.com

Talk to our engineers +61 2 9519 1200 · info@mibattery.com.au · mibattery.com.au