








Stock Code	Model No.	Specifications			Charge		Discharge		Dimensions				Weight (kg)	Assembly	Connection				Ingress Protection Rating	Orientation
		Voltage (V)	Capacity @5hr (Ah)	Watt Hour (Wh)	Voltage Max. (V)	Current Max. (A)	Cut-off Voltage (V)	Current Max. (A)	W mm	D mm	H mm	HT mm			Terminal Type	Torque Settings	Series (Max)	Parallel		
<b>CYLINDRICAL CELLS INSIDE</b>																				
89006-000	6LFP0.6	6.4	0.6	3.84	7.30	0.6	4.0	1.2	53.2	15	33	33	0.044	2S1P-Cyl	CE-HEXT		N/A	N/A	N/A	Any
89006-003	6LFP3.8	6.4	3.8	24.32	7.30	3.8	5.0	5	70	47.5	101	108	0.29	2S1P-Cyl	F1 (Faston 187)		Up to 4S	No	IP64	Any
89006-015	6LFP7.6	6.4	7.6	48.64	7.30	7.6	5.0	8	150	35	93	101.2	0.4	2S2P-Cyl	F1 (Faston 187)		Up to 4S	No	IP65	Any
89006-016	6LFP11.4	6.4	11.4	72.96	7.30	10	5.0	10	150	50	93	101.2	0.6	2S3P-Cyl	F2 (Faston 250)		Up to 4S	No	IP65	Any
89006-004	12LFP3.8	12.8	3.8	48.64	14.60	3.8	10.0	5	90	70	101	108	0.5	4S1P-Cyl	F1 (Faston 187)		Up to 4S	No	IP65	Any
89006-005	12LFP7.2	12.8	7.2	92.16	14.60	7.2	10.0	10	151	65	94	101	0.95	4S2P-Cyl	F2 (Faston 250)		Up to 4S	No	IP65	Any
89006-026	12LFP7.6	12.8	7.6	97.28	14.60	5	8.4	10	90	70	101	108	0.9	4S2P-Cyl	F2 (Faston 250)		Up to 4S	No	IP65	Any
89006-006	12LFP10.8	12.8	10.8	138.24	14.60	10	10.0	10	151	99	94	99	1.5	4S3P-Cyl	F2 (Faston 250)		Up to 4S	No	IP65	Any
89006-019	12LFP11.4	12.8	11.4	145.92	14.60	10	10.0	10	151	65	94	101	1.3	4S3P-Cyl	F2 (Faston 250)		Up to 4S	No	IP65	Any
89006-020	12LFP15.2	12.8	15.2	194.56	14.60	15	10.0	15	151	99	94	100	1.7	4S4P-Cyl	F2 (Faston 250)		Up to 4S	No	IP65	Any
89006-007A	12LFP24	12.8	24	307.2	14.60	20	8.4	20	181	76.5	166.8	166.8	2.9	4S6P-Cyl	F6 (M5 Bolt)	3.2 N.m	Up to 4S	No	IP54	Any
89006-018	12LFP28	12.8	28.8	368.64	14.60	28.8	10.0	30	176	166	125	125	3.6	4S8P-Cyl	F8 (M6 Bolt)	4.2 N.m	Up to 4S	No	IP65	Any
89006-017	12LFP30	12.8	30.4	389.12	14.60	30	10.0	30	165.5	125	174	174	3.72	4S8P-Cyl	F8 (M6 Bolt)	4.2 N.m	Up to 4S	No	IP65	Any
89006-002A	12LFP36	12.8	36	460.8	14.60	36	10.0	36	195	133	170	170	4.43	4S10P-Cyl	F8 (M6 Bolt)		Up to 4S	No	IP65	Any
89006-009A	12LFP42HR	12.8	42	537.6	14.60	42	10.0	100	198	166	169	169	6.3	4S14P-Cyl	F18 (M8 Bolt)	8.2 N.m	Up to 4S	No	IP66	Any
89006-002B	12LFP45	12.8	45.6	583.68	14.60	40	10.0	40	195	133	170	170	5.5	4S12P-Cyl	F8 (M6 Bolt)	4.2 N.m	Up to 4S	No	IP67	Any
89006-009	12LFP48	12.8	47.6	609.28	14.60	48	10.0	50	198	166	169	169	6.1	4S14P-Cyl	F18 (M8 Bolt)	8.2 N.m	Up to 4S	No	IP65	Any
89006-011	12LFP75	12.8	74.8	957.44	14.60	75	10.0	75	260	168	211	216	9.65	4S22P-Cyl	F18 (M8 Bolt)	8.2 N.m	Up to 4S	No	IP64	Any
89006-001A	12LFP108	12.8	108	1382.4	14.60	100	10.0	100	329	171	217	222.5	13.8	4S30P-Cyl	F18 (M8 Bolt)	8.2 N.m	Up to 4S	No	IP64	Any
89006-023	12LFP122	12.8	121.6	1556.48	14.60	80	10.0	80	329	171	217	222.5	14.36	4S32P-Cyl	F18 (M8 Bolt)	8.2 N.m	Up to 4S	No	IP64	Any
89006-027	24LFP4	25.6	4	102	29.20	4	16.8	10	151	65	94	101	1	8S1P-Cyl	F2 (Faston 250)		Up to 2S	No	IP65	Any
89006-028	24LFP20	25.6	20	512	29.20	10	16.8	20	195	133	170	170	4.4	8S5P-Cyl	F8 (M6 Bolt)	4.2 N.m	Up to 2S	No	IP65	Any
89006-030	48LFP30	51.2	30	1536	57.60	30	40.0	50 / 30 <sup>(1)</sup>	195	133	170	170	11.1	16S2P-Cyl	F18 (M8 Bolt)	8.2 N.m	1S max.	Up to 4P	IP64	Any

Stock Code	Model No.	Specifications			Charge		Discharge		Dimensions				Weight (kg)	Assembly	Connection				Ingress Protection Rating	Orientation
		Voltage (V)	Capacity @5hr (Ah)	Watt Hour (Wh)	Voltage Max. (V)	Current Max. (A)	Cut-off Voltage (V)	Current Max. (A)	W mm	D mm	H mm	HT mm			Terminal Type	Torque Settings	Series (Max)	Parallel		
<b>PRISMATIC CELLS INSIDE</b>																				
89006-010	12LFP50P	12.8	50	640	14.60	50	10.0	50	229	138	210	216	5.95	4S1P-Pris	F8 (M6 Bolt)	4.2 N.m	Up to 4S	No	IP54	Upright
89006-012A	12LFP100PS	12.8	100	1280	14.60	100	10.0	100	329	171	217	222.5	11.4	4S2P-Pris	F18 (M8 Bolt)	8.2 N.m	Up to 4S	No	IP64	Upright
89006-014A	12LFP105PSL	12.8	105	1344	14.60	100	10.0	100	395	110	286	286	11.5	4S1P-Pris	F18 (M8 Bolt)	8.2 N.m	Up to 4S <sup>(1)</sup>	Up to 4P <sup>(2)</sup>	IP64	Upright
89006-013A	12LFP150PS	12.8	150	1920	14.60	150	10.0	150	406	173	211.8	240	16.6	4S3P-Pris	F18 (M8 Bolt)	8.2 N.m	Up to 4S	Up to 2P <sup>(3)</sup>	IP64	Upright
89006-008	12LFP200P	12.8	200	2560	14.60	150	10.0	150	490	170	240	240	21.5	4S4P-Pris	F18 (M8 Bolt)	8.2 N.m	Up to 4S	Up to 2P <sup>(3)</sup>	IP64	Upright
89006-008A	12LFP200PHR	12.8	200	2560	14.60	200	8.4	200	485	170	240	240	21.2	4S4P-Pris	F18 (M8 Bolt)	8.2 N.m	Up to 4S	Up to 2P <sup>(3)</sup>	IP64	Upright
89006-024	12LFP300P	12.8	300	3840	14.60	200	8.4	200	520	240	220	223.2	30.5	4S3P-Pris	F18 (M8 Bolt)	8.2 N.m	Up to 4S	Up to 2P <sup>(3)</sup>	IP64	Upright
89006-021	24LFP50P	25.6	50	1280	29.20	50	20.0	50	329	171	217	222.5	11.1	8S1P-Pris	F18 (M8 Bolt)	8.2 N.m	Up to 2S	No	IP64	Upright
89006-022	24LFP100P	25.6	100	2560	29.20	100	20.0	100	490	170	240	240	21.2	8S2P-Pris	F18 (M8 Bolt)	8.2 N.m	Up to 2S	No	IP64	Upright
89006-029	24LFP150P	25.6	150	3840	29.20	150	16.8	150	532	208	215	218.5	27.32	8S1P-Pris	F18 (M8 Bolt)	8.2 N.m	Up to 2S	No	IP64	Upright
89006-025	36LFP100P	38.4	100	3840	43.80	100	26.4	100	520	240	220	223.2	29.9	12S1P-Pris	F18 (M8 Bolt)	8.2 N.m	1S max.	No	IP64	Upright
<b>GOLF RANGE</b>																				
89006-231A	12LFP18TB <sup>A</sup>	12.8	18	230.4	14.60	5	10.0	25	168	127.6	76	101.3	2.5	4S5P-Cyl	T-Bar to ADS PP* + Lotus Port		1S max.	No	IP54	Any
89006-234A	12LFP25TB <sup>A</sup>	12.8	25.2	322.56	14.60	5	10.0	30	168	127.6	102	127.8	2.8	4S7P-Cyl	T-Bar to ADS PP* + Lotus Port		1S max.	No	IP54	Any
89006-239A	12LFP32	12.8	32.4	414.72	14.60	30	10.0	30	175	175	110	113	3.6	4S9P-Cyl	F18 (M8) to ADS PP		1S max.	No	IP54	Any

**TERMINAL TYPE**



(1)50A max cont discharge (standalone use) or 30A max cont discharge (parallel use). (2)For this model, Series/Parallel connection allowable is max 4S or 4P, but the max total discharge current should not exceed 100A after parallel connection. (3)Refer to installation instructions for parallel installation. <sup>A</sup>This model comes with a charger. \*ADS PP = Anderson Powerpole connector. Ingress Protection Rating: IP5x = Dust protected. IP6x = Dust tight. Before using Drypower Rechargeable Lithium LiFePO4 batteries, please read the user guides and/or datasheets available at [www.drypower.com.au](http://www.drypower.com.au). This reference chart is to be used as a guide only. Performance may vary depending on application. All specifications are correct at time of creation. No guarantee is intended or implied by this data. Please refer to each model's respective datasheet for more detailed information. CAUTION: Do not short circuit. Do not crush. Do not heat or incinerate. Do not immerse in any liquid. Do not disassemble. Do not allow the battery to become overdischarged or leave in a discharged state. Always recharge after use and only use a Drypower approved LiFePO4 charger. Do not use chargers designed for other chemistries. Store at 50% capacity and recharge every 3 months. No parallel connection is allowed except for models where indicated. Series use only as indicated. Tampering and/or unauthorised removal of top plate will void warranty.