

FUJITSU



ALL NEW BATTERY CHARGERS FOR RECHARGEABLE NiMH

- » CHARGE UP TO 4 CELLS AT A TIME
- » INCLUDES 4 x AA NiMH BATTERIES MADE IN JAPAN
- » BUILT IN CHARGE SAFETY FEATURES



Available at Master Instruments
Official Partner and Distributor



BATTERY CHARGERS FOR AA / AAA NiMH

Fujitsu chargers are designed with built in intelligent safety features to prevent damage and prolong the service life of your AA and AAA NiMH batteries.

Features of Fujitsu NiMH battery chargers

- **Multiple safety features** including reverse polarity detection, primary (non-rechargeable) cell detection, over temperature detection, overdischarge detection, and negative delta V ($-\Delta V$) detection.
- **LED status indicators** - Red LEDs turn on when charging, switch off when complete or flash to indicate an error.
- **Auto shut off** to protect batteries from damage when charge is complete.



QUICK CHARGER (for 1-4 AA / AAA Cells)

Fast charger with individual charging channels means batteries with different states of charge can be charged simultaneously without a hassle. Once a battery reaches full charge that channel will automatically switch off while the other channels continue.

Specifications Model: FCT344FX0ST

- Suitable for: Charges 1-4 cells (AA & AAA NiMH)
- Input voltage: 100-240VAC 50/60Hz
- Charge current: AA @1100mA (1-2 cells); @550mA (3-4 cells)
AAA @560mA (1-2 cells); @280mA (3-4 cells)
- Dimensions: 108(L) x 68(W) x 28(H) mm
- Weight: 100g approx.

No. of Cells	Charge Time*
1 to 2	1.5 - 2 hours
3 to 4	3 - 4 hours

*Charge times approx. for AA 1900mAh (min.), AAA 750mAh (min.)

Includes
4 x HR-3UTC AA
2100 cycle
LSD batteries



SRP \$59.95



BASIC CHARGER (for 2 or 4 AA / AAA Cells)

Standard overnight charger for charging 2 or 4 cells at a time. 2 x LED status indicators (one for each pair of cells) help identify when charging is complete. Safety features include reverse polarity protection, auto shut off and bad cell detection.

Specifications Model: FCT345FX0ST

- Suitable for: Charges 2 or 4 cells (AA & AAA NiMH)
- Input voltage: 100-240VAC 50/60Hz
- Charge current: AA @330mA (AA min. 1900mAh)
AAA @160mA (AAA min. 750mAh)
- Dimensions: 108(L) x 68(W) x 28(H) mm
- Weight: 100g approx.

Cell Size	Charge Time*
AA (2 or 4)	6 hours
AAA (2 or 4)	5 hours

*Charge times approx. for AA 1900mAh (min.), AAA 750mAh (min.)

Includes
4 x HR-3UTC AA
2100 cycle
LSD batteries



SRP \$39.95